

1. Casing - OCTG

Size		OD (mm)	Weight (kg/m)	Wall Thickness (mm)	Type of end							
in	mm				H40	J55 K55	M65	L80 C95	N80	C90 T95	P110	Q125
4 1/2	9.50	114.30	14.14	5.21	PS	PS	PS	-	-	-	-	-
4 1/2	10.50	114.30	15.63	5.69	-	PSB	PSB	-	-	-	-	-
4 1/2	11.60	114.30	17.26	6.35	-	PSLB	PLB	PLB	PLB	PLB	PLB	-
4 1/2	13.50	114.30	20.09	7.37	-	-	PLB	PLB	PLB	PLB	PLB	-
4 1/2	15.10	114.30	22.47	8.56	-	-	-	-	-	-	PLB	PLB
5	11.50	127.00	17.11	5.59	-	PS	PS	-	-	-	-	-
5	13.00	127.00	19.35	6.43	-	PSLB	PSLB	-	-	-	-	-
5	15.00	127.00	22.32	7.52	-	PSLBE	PLB	PLBE	PLBE	PLBE	PLBE	-
5	18.00	127.00	26.79	9.19	-	-	PLB	PLBE	PLBE	PLBE	PLBE	PLBE
5	21.40	127.00	31.85	11.10	-	-	PLB	PLB	PLB	PLB	PLB	PLB
5	23.20	127.00	34.53	12.14	-	-	-	PLB	PLB	PLB	PLB	PLB
5	24.10	127.00	35.86	12.70	-	-	-	PLB	PLB	PLB	PLB	PLB
5 1/2	14.00	139.70	20.83	6.20	PS	PS	PS	-	-	-	-	-
5 1/2	15.50	139.70	23.07	6.98	-	PSLBE	PSLB	-	-	-	-	-
5 1/2	17.00	139.70	25.30	7.72	-	PSLBE	PLB	PLBE	PLBE	PLBE	PLBE	-
5 1/2	20.00	139.70	29.76	9.17	-	-	PLB	PLBE	PLBE	PLBE	PLBE	-
5 1/2	23.00	139.70	34.23	10.54	-	-	PLB	PLBE	PLBE	PLBE	PLBE	PLBE
5 1/2	26.80	139.70	39.88	12.70	-	-	-	-	-	P	-	-
5 1/2	29.70	139.70	44.20	14.27	-	-	-	-	-	P	-	-
5 1/2	32.60	139.70	48.51	15.88	-	-	-	-	-	P	-	-
5 1/2	35.30	139.70	52.53	17.45	-	-	-	-	-	P	-	-
5 1/2	38.00	139.70	56.55	19.05	-	-	-	-	-	P	-	-
5 1/2	40.50	139.70	60.27	20.62	-	-	-	-	-	P	-	-
5 1/2	43.10	139.70	64.14	22.22	-	-	-	-	-	P	-	-
6 5/8	20.00	168.28	29.76	7.32	PS	PSLB	PSLB	-	-	-	-	-
6 5/8	24.00	168.28	35.72	8.94	-	PSLBE	PLB	PLBE	PLBE	PLBE	PLBE	-
6 5/8	28.00	168.28	41.67	10.59	-	-	PLB	PLBE	PLBE	PLBE	PLBE	-
6 5/8	32.00	168.28	47.62	12.06	-	-	-	PLBE	PLBE	PLBE	PLBE	PLBE
7	17.00	177.80	25.30	5.87	PS	-	-	-	-	-	-	-
7	20.00	177.80	29.76	6.91	PS	PS	PS	-	-	-	-	-
7	23.00	177.80	34.23	8.05	-	PSLBE	PLB	PLBE	PLBE	PLBE	-	-
7	26.00	177.80	38.69	9.19	-	PSLBE	PLB	PLBE	PLBE	PLBE	PLBE	-
7	29.00	177.80	43.16	10.36	-	-	PLB	PLBE	PLBE	PLBE	PLBE	-
7	32.00	177.80	47.62	11.51	-	-	PLB	PLBE	PLBE	PLBE	PLBE	-
7	35.00	177.80	52.09	12.65	-	-	-	PLBE	PLBE	PLBE	PLBE	PLBE
7	38.00	177.80	56.55	13.72	-	-	-	PLBE	PLBE	PLBE	PLBE	PLBE



7	42.70	177.80	63.54	15.88	-	-	-	-	-	P	-	-
7	46.40	177.80	69.05	17.45	-	-	-	-	-	P	-	-
7	50.10	177.80	74.56	19.05	-	-	-	-	-	P	-	-
7	53.60	177.80	79.77	20.62	-	-	-	-	-	P	-	-
7	57.10	177.80	84.97	22.22	-	-	-	-	-	P	-	-
7 5/8	24.00	193.68	35.72	7.62	PS	-	-	-	-	-	-	-
7 5/8	26.40	193.68	39.29	8.33	-	PSLBE	PSLB	PLBE	PLBE	PLBE	-	-
7 5/8	29.70	193.68	44.20	9.52	-	-	PLB	PLBE	PLBE	PLBE	PLBE	-
7 5/8	33.70	193.68	50.15	10.92	-	-	PLB	PLBE	PLBE	PLBE	PLBE	-
7 5/8	39.00	193.68	58.04	12.70	-	-	-	PLBE	PLBE	PLBE	PLBE	PLBE
7 5/8	42.80	193.68	63.69	14.27	-	-	-	PLB	PLB	PLB	PLB	PLB
7 5/8	45.30	193.68	67.41	15.11	-	-	-	PLB	PLB	PLB	PLB	PLB
7 5/8	47.10	193.68	70.09	15.88	-	-	-	PLB	PLB	PLB	PLB	PLB
7 5/8	51.20	193.68	76.19	17.45	-	-	-	-	-	P	-	-
7 5/8	55.30	193.68	82.30	19.05	-	-	-	-	-	P	-	-
7 3/4	46.10	196.85	68.60	15.11	-	-	-	P	P	P	P	P
8 5/8	24.00	219.08	35.72	6.71	PS	PS	PS	-	-	-	-	-
8 5/8	28.00	219.08	41.67	7.72	PS	-	PS	-	-	-	-	-
8 5/8	32.00	219.08	47.62	8.94	PS	PSLBE	PSLB	-	-	-	-	-
8 5/8	36.00	219.08	53.57	10.16	-	PSLBE	PSLB	PLBE	PLBE	PLBE	-	-
8 5/8	40.00	219.08	59.53	11.43	-	-	PLB	PLBE	PLBE	PLBE	PLBE	-
8 5/8	44.00	219.08	65.48	12.70	-	-	-	PLBE	PLBE	PLBE	PLBE	- PLBE
8 5/8	49.00	219.08	72.92	14.15	-	-	-	PLBE	PLBE	PLBE	PLBE	-
9 5/8	32.30	244.48	48.07	7.92	PS	-	-	-	-	-	-	-
9 5/8	36.00	244.48	53.57	8.94	PS	PSLB	-	-	-	-	-	-
9 5/8	40.00	244.48	59.53	10.03	-	PSLBE	PSLB	PLBE	PLBE	PLBE	-	-
9 5/8	43.50	244.48	64.73	11.05	-	-	PSLB	PLBE	PLBE	PLBE	PLBE	-
9 5/8	47.00	244.48	69.94	11.99	-	-	PLB	PLBE	PLBE	PLBE	PLBE	PLBE
9 5/8	53.50	244.48	79.62	13.84	-	-	PLB	PLBE	PLBE	PLBE	PLBE	PLBE
9 5/8	58.40	244.48	86.91	15.11	-	-	-	PLB	PLB	PLB	PLB	PLB
9 5/8	59.40	244.48	88.40	15.47	-	-	-	-	-	P	-	-
9 5/8	64.90	244.48	96.58	17.07	-	-	-	-	-	P	-	-
9 5/8	70.30	244.48	104.62	18.64	-	-	-	-	-	P	-	-
9 5/8	75.60	244.48	112.50	20.24	-	-	-	-	-	P	-	-
10 3/4	32.75	273.05	48.74	7.09	PS	-	-	-	-	-	-	-
10 3/4	40.50	273.05	60.27	8.89	PS	PSB	PSB	-	-	-	-	-
10 3/4	45.50	273.05	67.71	10.16	-	PSBE	PSB	-	-	-	-	-
10 3/4	51.00	273.05	75.90	11.43	-	PSBE	PSB	PSBE	PSBE	PSBE	PSBE	-
10 3/4	55.50	273.05	82.59	12.57	-	-	PSB	PSBE	PSBE	PSBE	PSBE	-
10 3/4	60.70	273.05	90.33	13.84	-	-	-	-	-	PSBE	PSBE	PSBE
10 3/4	65.70	273.05	97.77	15.11	-	-	-	-	-	PSB	PSB	PSB
10 3/4	73.20	273.05	108.93	17.07	-	-	-	-	-	P	-	-
10 3/4	79.20	273.05	117.86	18.64	-	-	-	-	-	P	-	-



10 ³ / ₄	85.30	273.05	126.94	20.24	-	-	-	-	-	P	-	-
11 ³ / ₄	42.00	298.45	62.50	8.46	PS	-	-	-	-	-	-	-
11 ³ / ₄	47.00	298.45	69.94	9.53	-	PSB	PSB	-	-	-	-	-
11 ³ / ₄	54.00	298.45	80.36	11.05	-	PSB	PSB	-	-	-	-	-
11 ³ / ₄	60.00	298.45	89.29	12.42	-	PSB	PSB	PSB	PSB	PSB	PSB	PSB
11 ³ / ₄	65.00	298.45	96.73	13.56	-	-	-	P	P	P	P	P
11 ³ / ₄	71.00	298.45	105.66	14.78	-	-	-	P	P	P	P	P
13 ³ / ₈	48.00	339.72	71.43	8.38	PS	-	-	-	-	-	-	-
13 ³ / ₈	54.50	339.72	81.10	9.65	-	PSB	PSB	-	-	-	-	-
13 ³ / ₈	61.00	339.72	90.78	10.92	-	PSB	PSB	-	-	-	-	-
13 ³ / ₈	68.00	339.72	101.19	12.19	-	PSB	PSB	PSB	PSB	PSB	PSB	-
13 ³ / ₈	72.00	339.72	107.15	13.06	-	-	-	PSB	PSB	PSB	PSB	PSB
16	65.00	406.40	96.73	9.53	PS	-	-	-	-	-	-	-
16	75.00	406.40	111.61	11.13	-	PSB	PSB	-	-	-	-	-
16	84.00	406.40	125.01	12.57	-	PSB	PSB	-	-	-	-	-
16	109.00	406.40	162.21	16.66	-	P	-	P	P	-	P	P
18 ⁵ / ₈	87.50	473.08	130.21	11.05	PS	PSB	PSB	-	-	-	-	-
20	94.00	508.00	139.89	11.13	PSL	PSLB	PSLB	-	-	-	-	-
20	106.50	508.00	158.49	12.70	-	PSLB	PSLB	-	-	-	-	-
20	133.00	508.00	197.93	16.13	-	PSLB	-	-	-	-	-	-

Remarks: P–Plain end; S–Short round thread; L–Long round thread; B–Buttress thread; E–Extreme-line.