

1. Float Valve & Float Valve Sub

Float Valve Sub				
Model	OD mm(inch)	ID mm(inch)	Conn.	Float Valve Type
FZF83	82.6(3 1/4)	31.8(1 1/4)	NC23 B×2 3/8REG B	1R
FZF105	104.8(4 1/8)	31.8(1 1/4)	NC31 B×2 7/8REG B	1F-2R
FZF127	127(5)	50.8(2)	3 1/2REG B×NC38 B	2F-3R
FZF178	178(7)	71.4(2 13/16)	4 1/2REG B×NC50 B	4R
FZF165	165(6 1/2)	71.4(2 13/16)	NC50(B×P)	5R
FZF203	203(8)	71.4(2 13/16)	6 5/8REG B×6 5/8REG B	5F-6R
FZF229/FZF241	229(9)/241(9 1/2)	76.2(3)	7 5/8REG B×7 5/8REG B	5F-6R

Float Valve							
Model	OD mm(inch)	OAL mm(inch)	ID mm(inch)	Box Conn.		Other Connections	
				Conn.	Bore Depth mm(inch)	Conn.	Bore Depth mm(inch)
1R	42.1(1 21/32)	149.2(5 7/8)	42.9(1 11/16)	2 3/8REG	231.8(9 1/8)	NC23	231.8(9 1/8)
1F-2R	48.4(1 29/32)	158.8(6 1/4)	49.21(1 15/16)	2 7/8REG	254(10)	NC26	241.3(9 1/2)
2F-3R	61.1(2 13/32)	165.1(6 1/2)	61.9(2 7/16)	3 1/2REG	266.7(10 1/2)	NC31	260.35(10 1/4)
3F	71.4(2 13/16)	254(10)	72.2(2 27/32)			3 1/2FH	355.6(14)
3 1/2F	79.4(3 1/8)	254(10)	80.2(3 5/32)			NC38	362(14 1/4)
4R	88.1(3 15/32)	211.1(8 5/16)	88.9(3 1/2)	4 1/2REG	325.4(12 13/16)	NC44	331.8(13 1/16)
4F	92.8(3 21/32)	304.8(12)	93.7(3 11/16)			NC46	425.4(16 3/4)
5R	98.4(3 7/8)	247.6(9 3/4)	99.2(3 29/32)	5 1/2REG	374.6(14 3/4)	NC50	368.3(14 1/2)
5F-6R	121.4(4 25/32)	298.4(11 3/4)	122.2(4 13/16)	7 5/8REG	438.2(17 1/4)	5 1/2FH	431.8(17)